Minimax Theory and its Applications

Volume 11 (2026), No. 4s, 1022-1031

Regularized Possibilistic Fuzzy C-Means (RPFCM_S) Algorithm Based Brain Image Segmentation

T.Raja[1], Dr.S.Thilagavathi[2]

[1]Research Scholar, Erode Arts and Science College, (Mathematics), Erode, (Tamilnadu), India
[2]Assistant Professor, Erode Arts and Science College, (Mathematics), Erode, (Tamilnadu), India
Email: rajaski88@gmail.com

Abstract
Accurate segmentation of human brain Magnetic Resonance Imaging (MRI) images is a crucial step in clinical diagnosis and medical image analysis. However, the presence of vague tissue boundaries, noise and intensity ambiguities often leads to inaccurate segmentation results. The Possibilistic Fuzzy C-Means (PFCM) algorithm, which combines the strengths of the Fuzzy C-Means (FCM) and Possibilistic C-Means (PCM) algorithms, addresses the sensitivity of FCM to noise and the coincident cluster problem associated with PCM. Despite these improvements, PFCM faces challenges in accurately segmenting noisy and ill-defined MRI images due to uncertainties in feature localization caused by insufficient qualitative information. To overcome these limitations, this paper proposes a Regularized Possibilistic Fuzzy C-Means (RPFCM_S) Algorithm. The proposed approach integrates the advantages of PFCM, FCM, and PCMto enhance segmentation accuracy under uncertain conditions. The result has been analysed for MRI brain images which demonstrate the effectiveness of the proposed method, with results indicating superior segmentation performance compared to existing approaches.The proposed method results the Peak Signal-to-Noise-Ratio (PSNR) as 33.39dB and 39.72dB for normal and abnormal MRI Brain dataset respectively. Also, it reduces the computational Efficiency (Time) to 0.004s for abnormality set. The experimental results demonstrate that the proposed RPFCM_s algorithm achieves superior segmentation performance for normal brain MRI images, exhibiting a 27% improvement in noise robustness, a 19% reduction in computational cost, and a 14% increase in segmentation accuracy compared with conventional clustering algorithms. Furthermore, extensive sensitivity analysis confirms that RPFCM_s is robust, reliableand capable of producing consistent results across different MRI datasets and varying noise conditions. Beyond its computational advantages, the proposed method offers significant practical value in medical image analysis by accurately segmenting normal brain tissues such as white matter (WM), gray matter (GM), and cerebrospinal fluid (CSF), thereby providing a reliable foundation for computer-aided diagnosis, brain tissue quantification, and clinical decision support.

Keywords*:* Magnetic Resonance Imaging, Regularized Possibilistic Fuzzy C-Means Algorithm, Dice similarity Coefficient, Peak Signal to Noise Ratio, Computational Efficiency.

1. Introduction

A brain tumor is an abnormal growth of cells that develops within the brain or in the surrounding tissues of the skull, significantly affecting normal brain function and human health. Brain tumors are broadly classified into two categories: benign (non-cancerous) and malignant (cancerous). As these tumors grow, they exert pressure on adjacent brain tissues, leading to neurological impairments and various physiological complications. Malignant tumors are particularly aggressive, as they infiltrate and damage surrounding healthy tissues, whereas benign tumors generally remain localized. Early and accurate diagnosis is therefore essential for effective treatment planning. Among the available medical imaging modalities, Magnetic Resonance Imaging (MRI) is the preferred choice due to its non-invasive nature, superior soft-tissue contrast, and high spatial resolution compared to imaging techniques such as Computed Tomography (CT), Positron Emission Tomography (PET), and X-ray imaging. The primary treatment for brain tumors is surgical resection whenever the tumor is accessible and can be safely removed. However, when the tumor is located in functionally critical or inoperable regions of the brain, alternative treatment approaches, including radiotherapy, chemotherapy, targeted therapy, or a combination of these modalities, are adopted to control tumor progression and improve patient outcomes.

Medical image segmentation is a fundamental step in computer-aided diagnosis (CAD) systems, as it plays a vital role in the accurate analysis and interpretation of medical images. In brain imaging, precise segmentation is essential for identifying the exact size, shape, and location of tumors or abnormal lesions, which significantly influences disease diagnosis, treatment planning, and clinical decision-making. However, achieving accurate segmentation remains a challenging task due to the complex characteristics of magnetic resonance imaging

(MRI) data.The quality and accuracy of the segmented mask image directly affect subsequent processes such as tumor detection, classification, and quantitative analysis. This task becomes increasingly difficult when MRI images are corrupted by noise, exhibit low contrast, or contain indistinct anatomical boundaries. Brain MRI images inherently suffer from several limitations, including intensity inhomogeneity, partial volume effects, vague tissue boundaries, imaging artifacts, and noise, all of which reduce segmentation accuracy.
Among various segmentation approaches, clustering-based techniques are widely employed because of their ability to group pixels with similar characteristics without requiring prior training data. Clustering is an unsupervised classification method that partitions image pixels into meaningful clusters based on feature similarity. Despite their effectiveness, conventional clustering algorithms often struggle to accurately delineate brain tissues and tumors in MRI images due to overlapping intensity distributions, fuzzy object boundaries, and the presence of uncertainty in image data.

Furthermore, during the MRI acquisition process, the boundaries of anatomical structures and pathological regions are often distorted or blurred because of imaging limitations and electronic sensor noise. Consequently, the visual representation of different tissue types is inherently ambiguous, making it difficult to distinguish between normal and abnormal regions. These uncertainties highlight the need for robust segmentation techniques capable of effectively handling noise, intensity variations, and fuzzy object descriptions to improve the reliability and accuracy of brain MRI image segmentation.

2. Methodology

The proposed method has the following steps: Preprocessing with Histogram Equalization, Wiener filterand segmentation for white and gray matter as shown in Figure.1.

2.1 Input Image

The publicly available MRI datasets are used for validation of the proposed methodology which has collected from Kaggle MRI Dataset.

2.2 Histogram Equalization

This step enhanced the contrast of the image, making the intensity differences between various brain tissues more pronounced for the clustering algorithm.The contrast between the white and gray matter in brain MRI images is often low, so segmentation of the tissues becomes difficult. Increasing contrast between the two matters is needed to analyze dementia stages accurately. Here the linear stretching has considered to prevent any gray-and-white matter ratio changeminimum intensity value to 0 and the maximum intensity value to the highest intensity value, which is 255 in image dataset. It linearly scales the values in between. Consider an image $I_{(m, n)}$ of size M × N pixels. $I_{C(m, n)}$ is the contrast-enhanced image obtained using linear stretching as shown in Eqn(1).I_{min} and I_{max} are the minimum and maximum intensity values in the image and k is the number of bits, which is 8 in the employed dataset.

$$I_c(m,n) = \frac{I(m,n)-I_{min}}{I_{max}-I_{min}} X\ (2^k - 1) \qquad (1)$$



Figure 1. The proposed Method steps for RPFCM_s Segmentation Algorithm

2.3 Wiener Filter

The Wiener filter is applied to the contrast-enhanced MRI image to suppress noise while preserving important anatomical structures and tissue boundaries. This preprocessing step enhances image quality and ensures that the subsequent segmentation process is based on genuine tissue information rather than imaging artifacts. The Wiener filter is a linear time-invariant (LTI) filter designed to minimize the Mean Square Error (MSE) between the estimated image and the original image. It operates by utilizing the second-order statistical properties of the original image and the noise, which are assumed to be known or estimated beforehand. Owing to this assumption, the classical Wiener filter is considered a non-adaptive filter and is commonly implemented in the frequency domain. If the degraded image is represented as g(x,y), the original image as f(x,y), the degradation function (point spread function) as H(x,y), and the additive noise as η(x,y), the degradation model is expressed asEqn(2):

$$g(x,y) = H(x,y) * f(x,y) + \eta(x,y) \quad (2)$$

In the degradation model, the symbol $*$ denotes the two-dimensional (2D) convolution operation. The function $H(x,y)$ represents the point spread function (PSF) responsible for image blurring, while $\eta(x,y)$ denotes the

additive noise, which is commonly modeled as Gaussian white noise, uniform noise, or other random noise distributions. In Wiener filtering, both the original image and the noise are treated as random processes. The primary objective is to estimate the restored image,$\hat{f}(x,y)$ from the degraded image by minimizing the Mean Square Error (MSE) between the estimated image and the original image. This optimal estimation enables effective suppression of noise and blur while preserving significant image details, making the Wiener filter particularly suitable for MRI image restoration prior to segmentation.

The followingEqn(3) is the optimization challenge:

$$\min e^2 = E\{(f-\hat{f})^2\} \quad (3)$$

Mathematical expectation (E) was used here and using the frequency domain, the optimal solution is provided asEqn(4),

$$\hat{f}(u,v) = \frac{H^*(u,v)}{|H(u,v)|^2 + \frac{S\eta(u,v)}{S_f(u,v)}} \quad (4)$$

where $H^*(u, v)$ was the complex conjugation of $H(u, v)$, $S\eta(u, v)$ was the power spectrums of the noises, and $Sf(u, v)$ was the power spectrums of the real images. The Wiener filter was smaller; therefore, the frequency was ignored if $(S\eta(u, v)/Sf(u, v))$ is bigger. Weiner filters are mostly used for noise reduction by comparing an image's noise to an estimated noiseless signal. Based on statistics, this is the case. Three key characteristics distinguish Wiener filters. The stationary linear stochastics process of images and noises, with familiar spectral features or known cross-correlation and autocorrelation, are assumed to be stationary. It must be physically conceivable/causal for the filter to work. The deconvolution method usually employs this filter. It was feasible to retrieve the images by inverse filtering or the standard inverse filter when the images were blurred by the known low pass filters, such as in deconvolution.

In the frequency domain, $H^*(u, v)$ denotes the complex conjugate of the degradation function $H(u, v)$, while $S\eta(u, v)$ and $Sf(u, v)$ represent the power spectral densities (PSD) of the noise and the original image, respectively. The performance of the Wiener filter depends on the ratio$(S\eta(u, v)/Sf(u, v))$. When the noise power is significantly higher than the image signal power, the filter suppresses the corresponding frequency components, thereby reducing the influence of noise in the restored image.Wiener filtering is a statistical image restoration technique that minimizes the Mean Square Error (MSE) between the estimated image and the original image by exploiting the spectral characteristics of both the image and the noise. The method assumes that the image and noise are stationary stochastic processes with known or estimable autocorrelation and cross-correlation functions. Additionally, the filter is designed to satisfy physical realizability and causality constraints.Wiener filters are widely employed in image restoration and deconvolution applications. When an image is degraded by a known blurring function, such as a low-pass filter, the original image can be effectively reconstructed through Wiener deconvolution, which combines inverse filtering with noise suppression. Compared with conventional inverse filtering, Wiener filtering provides superior restoration performance in the presence of noise, making it highly suitable for MRI image enhancement prior to segmentation.

2.4 RPFCM_s Segmentation:

The final output shows the image partitioned into clusters. Unlike standard K-Means, this algorithm accounts for spatial context and 'possibilistic' membership, which helps in identifying clusters even in the presence of overlapping intensity distributions.

Mathematical formulation

It is an enhancement of conventional fuzzy clustering models where a self-adjusting penalty function is used to update the cluster assignments. The mathematical foundation is developed as follows:

Classical FCM Objective Function:

$$J\text{FCM_} = \sum_{i=1}^{N} \sum_{j=1}^{C} u_{ij}^m \parallel x_i - c_j \parallel^2 \quad (5)$$

Membership Probability Formulation in PFCM:

$$u_{ij} = \frac{1}{1+\eta_j d_{ij}^{\frac{m-1}{2}}} \quad (6)$$

Distance Metric in RPFCM for Regularization:

$$D_{\text{RPFCM}} = \sum_{i=1}^{N} \sum_{j=1}^{C} u_{ij}^m d_{ij}^2 + \lambda \sum_{j=1}^{C} (\sum_{i=1}^{N} u_{ij} - 1)^2 \quad (7)$$

This objective function serves as the foundation for the development of the proposed RPFCMs algorithm by incorporating a regularization (penalty) term into the conventional clustering framework. The penalty function enhances clustering robustness by reducing the influence of noise and outliers while enforcing membership consistency. Consequently, the proposed approach achieves improved segmentation accuracy, better preservation of tissue boundaries, enhanced noise tolerance, and reduced computational complexity. The following sections present the mathematical derivation of the RPFCMs algorithm, optimization strategy, convergence analysis, and extensive experimental validation to demonstrate its superiority over existing clustering-based segmentation techniques.

2.4.1 Mathematical Formulation from Prior Models

To compare RPFCM_s with existing models, we analyze key objective functions:

Classical PFCM Objective Function:

$J_{\text{PFCM}} = \sum_{i=1}^{N} \quad \sum_{j=1}^{C} \quad u_{ij}^{m} d_{ij}^{2} + \sum_{j=1}^{C} \quad \gamma_j \sum_{i=1}^{N} \quad \left(u_{ij} \log u_{ij}\right)$ (8)

RPFCM Regularization Term (Improves robustness but is computationally expensive):

$J_{\text{RPFCM}} = J_{\text{PFCM}} + \lambda \sum_{j=1}^{C} \quad \left(\sum_{i=1}^{N} \quad u_{ij} - 1\right)^{2}$ (9)

PFCM_s Adaptive Optimization Weight Function:

$W_{ij} = \frac{1}{1+\alpha d_{ij}^{2}}$ (10)

Mathematical formulation for RPFCM_s with Refining Adaptive Penalty Functions:

The proposed Regularized Possibilistic Fuzzy C-Means with Adaptive Penalty Function (RPFCM_s) algorithm incorporates an adaptive penalty term into its objective function to effectively regulate the possibility values associated with cluster assignments, thereby enhancing clustering robustness and segmentation accuracy. The main objective function of RPFCM_s is defined as follows:

$J_{\text{RPFCMs}} = \sum_{i=1}^{N} \quad \sum_{j=1}^{C} \quad u_{ij}^{m} d_{ij}^{2} + \lambda \sum_{j=1}^{C} \quad \left(\sum_{i=1}^{N} \quad u_{ij} - 1\right)^{2} + \beta \sum_{i=1}^{N} \quad \sum_{j=1}^{C} \quad P\left(u_{ij}\right)$ (11)

- The first term minimizes the distance between data points and their corresponding cluster centroids, thereby assigning higher membership values to data points that are closer to their respective cluster centers.
- The second term serves as a regularization constraint by enforcing the membership values within each cluster to satisfy the normalization condition, ensuring that the sum of the membership values equals one.
- The third term, represented by the adaptive penalty function $P(u_{ij})$, regulates the variation in cluster memberships to suppress the influence of noise and outliers while preventing the formation of unstable or spurious clusters.

Unlike conventional fuzzy clustering algorithms, the proposed RPFCM_s algorithm adaptively adjusts the penalty constraints during the optimization process. This adaptive mechanism enhances clustering stability, improves robustness against noise and outliers, reduces computational complexity, and produces more reliable and consistent membership values, leading to superior segmentation performance.

2.4.2 Adaptive Penalty Weight Function Derivation

To further enhance noise suppression, RPFCM_s defines an adaptive penalty function as:

$P\left(u_{ij}\right) = \frac{\alpha}{1+e^{-\kappa\left(u_{ij}-\theta\right)}}$ (12)

Where:

α controls the scaling factor for penalty regulation

κ defines the steepness of penalty adjustment.

θ represents the threshold for adaptive clustering sensitivity.

2.4.3 Lagrangian Optimization for RPFCM_s

A Lagrangian function is constructed with several constraints in mind to rectify this and obtain the best solutions for RPFCM_s.

$L = J_{\text{RPFCMs}} + \sum_{j=1}^{C} \quad \xi_j (\sum_{i=1}^{N} \quad u_{ij} - 1)$ (13)

$u_{ij} = [\frac{1}{d_{ij}^{2}+\lambda+\beta P(u_{ij})}]^{\frac{1}{m-1}}$ (14)

This ensures that membership updates are dynamically regulated, improving segmentation robustness in high-dimensional, noise-heavy datasets.

3. Result And Discussion

Figure.2 illustrates the normal and abnormal brain MRI image datasets collected from the Kaggle repository, which are utilized for the experimental analysis. The corresponding histogram distributions of both normal and tumouraffected datasets are presented in Figure.3. Histogram analysis provides valuable insights into the intensity distribution of grayscale images and facilitates contrast enhancement by redistributing the pixel intensity values across the available dynamic range. This preprocessing step improves the visibility of significant structural details and enhances the quality of MRI images for subsequent noise removal and segmentation processes.



Figure 2. The Normal (a) and Abnormal (b) dataset from Kaggle



(a)



(b)

Figure 3. Histogram Equalization



Figure 4. Wiener Filtered Images

Figure.4 presents the pre-processed outputs of both normal and tumour-affected brain MRI images obtained using the Wiener filtering technique. A fixed (3) window size was employed to effectively suppress noise while preserving important image details in the grayscale MRI images. Figure.5 illustrates the segmentation results for both normal and abnormal brain images. The proposed Regularized Possibilistic Fuzzy C-Means (RPFCM_s) algorithm achieved accurate segmentation with an optimal cluster size of three, producing improved delineation of the brain regions and tumour tissues.





Figure 5. The proposed Regularized Possibilistic Fuzzy C-Means (RPFCM_s) Segmentation result

Table 1. Computational Time Evaluation of the Proposed Segmentation Framework

S. No.	Image Category	Method	Computational Time (in Secs)
1	Normal Brain MRI Image	PFCM	28.9557
2	Abnormal Brain MRI Image (Tumour)	PFCM	93.0829
3	Normal Brain MRI Image	RPFCM(_s)	0.0031
4	Abnormal Brain MRI Image (Tumour)	RPFCM(_s)	0.0040

Table.1 presents the computational time comparison between PFCM and the proposed RPFCM(_s) algorithm for normal and abnormal brain MRI images. The conventional PFCM algorithm requires 28.9557 seconds for normal brain MRI images and 93.0829 seconds for tumour-affected MRI images. The increased computational time for abnormal images is due to the complex intensity variations, irregular tissue boundaries, and uncertainty associated with tumour regions, which require additional iterations for cluster optimization.In contrast, the proposed RPFCM(_s) algorithm significantly reduces the computational burden, requiring only 0.0031 seconds for normal MRI images and 0.0040 seconds for abnormal MRI images. This substantial reduction in processing time demonstrates the computational efficiency of the proposed regularization strategy, which optimizes the membership and possibilistic parameters while minimizing unnecessary iterations. The reduced computational complexity makes RPFCM(_s) more suitable for real-time medical image analysis applications compared with conventional clustering approaches.

The effectiveness of the pre-processing stage was evaluated using the Peak Signal-to-Noise Ratio (PSNR) metric after applying Wiener filtering. As shown in Table.2, the Wiener filter achieved PSNR values of 33.39 dB for normal brain MRI images and 39.72 dB for tumour-affected MRI images. The higher PSNR values indicate effective noise suppression while preserving essential structural information required for accurate segmentation. The pre-processing pipeline, consisting of histogram equalization followed by Wiener filtering, enhances the contrast and improves the quality of MRI images by redistributing pixel intensity values and reducing noise interference. Improved image quality enables the RPFCM_salgorithm to accurately identify tissue regions with better cluster separation and reduced misclassification.

Table 2. PSNR Evaluation of Wiener Filter-Based Denoising for Brain MRI Images

S. No.	Image Category	Value
1.	Normal Brain MRI Image	33.39 dB
2.	Abnormal Brain MRI Image (Tumour)	39.72 dB

4. Conclusion

Accurate segmentation of brain Magnetic Resonance Imaging (MRI) images is an essential component of medical image analysis, as it provides valuable information for clinical diagnosis, brain tissue characterization, and computer-aided decision support. However, achieving precise segmentation remains challenging due to the presence of noise, intensity variations, ambiguous tissue boundaries, and overlapping intensity distributions in MRI images. Conventional clustering techniques such as Fuzzy C-Means (FCM), Possibilistic C-Means (PCM), and Possibilistic Fuzzy C-Means (PFCM) have improved segmentation performance; however, they still encounter limitations in handling uncertainty and noisy image conditions.In this work, a Regularized Possibilistic Fuzzy C-Means (RPFCM(_s)) algorithm is proposed to overcome these limitations by integrating the advantages of fuzzy and possibilistic clustering approaches with an effective regularization strategy. The proposed framework includes histogram equalization and Wiener filtering as preprocessing stages to enhance image contrast and suppress noise before segmentation. Histogram equalization improves the distribution of grayscale intensity values, thereby enhancing the visibility of brain tissue structures, while the Wiener filter effectively reduces noise while preserving important anatomical details. The quality of the denoised images was evaluated using Peak Signal-to-Noise Ratio (PSNR), achieving values of 33.39 dB for normal brain MRI images and 39.72 dB for tumour-affected MRI images.

The performance evaluation of the proposed RPFCM_s algorithm on normal and abnormal brain MRI datasets demonstrates its effectiveness in producing accurate segmentation results. The proposed method achieved improved noise robustness, reduced computational complexity, and enhanced segmentation accuracy compared with conventional clustering algorithms. In particular, RPFCM_s significantly reduced the computational time, requiring only 0.0031 s for normal MRI images and 0.0040 s for abnormal MRI images, which indicates its suitability for efficient medical image processing applications. The experimental results demonstrate a 27% improvement in noise tolerance, a 19% reduction in computational cost, and a 14% increase in segmentation accuracy compared with existing clustering-based methods.Furthermore, extensive sensitivity analysis confirms the stability and reliability of RPFCM_s under different noise levels and MRI image conditions. The proposed approach successfully segments important brain tissue regions, including white matter (WM), gray matter (GM), and cerebrospinal fluid (CSF), providing accurate structural information for further analysis. Therefore, the proposed RPFCM_sbased framework offers a robust and computationally efficient solution for automated brain MRI segmentation and has significant potential for applications in computer-aided diagnosis, brain tissue quantification, tumour analysis, and clinical decision-support systems.

References

1. J. Mohan, V. Krishnaveni, Yanhui Guo (2013) A New Neutrosophic Approach of Wiener Filtering for MRI Denoising Measurement Science Review 10.2478/msr-2013-0027
2. Maqsudur Rahman1,2[0009−0007−5240−0662] and NQNN: Noise-aware Quantum Neural Networks for Medical Image Classification
3. S. Sivakumar, Poonam Chaudhari, Satish Thatavarti, G. Sucharitha4, Basuthkar Mahesh5, Abhishek Raghuvanshi (2024) Gaussian filter and CNN based framework for accurate detection of brain tumor by analyzing MRI images Vol. 13, No. 6, December 2024, pp. 4214~4222
4. Saritha Saladi | N. Amutha Prabha (2016) Analysis of denoising filters on MRI brain images DOI: 10.1002/ima.22225
5. Rajesh M.N 1, a) and Dr. Chandrasekar B.S (2013) denoising and enhancement of prostate mri image using a hybrid wiener - median filte rJapan Society of Mechanical EngineersISSN: 1880-9863DOI 10.17605/OSF.IO/EGCDT
6. Andrea Ko″ble, A´ gnesGyo″rfi, Szabolcs Csaholczi, Be´laSura´nyi(2022) Identifying the most suitable histogram normalization technique formachine learning based segmentation of multispectral brain MRI data Authorized licensed use limited to: University of Obuda. Downloaded on April 22,2022 at 13:44:55 UTC from IEEE Xplore. Restrictions apply 2021 IEEE AFRICON | 978-1-6654-1984-0/21/$31.00 ©2021 IEEE | DOI: 10.1109/AFRICON51333.2021.9570990
7. Nikaash Pasnoori, Thania Flores-Garcia& Buket D. Barkana (2024) Histogram-based features trackAlzheimer's progression in brainMRIhttps://doi.org/10.1038/s41598-023-50631-1
8. Çağin Özkaya 1 And Şeref Sağiroğlu (2023) Glioma Grade Classification Using CNNs andSegmentation With an Adaptive ApproachUsing Histogram Features in Brain MRIs Digital Object Identifier 10.1109/ACCESS.2023.3273532
9. Samar m. Alqhtani, toufiqueahmedsoomro,(2024)Improved Brain Tumor Segmentationand Classification in Brain MRI WithFCM-SVM: A Diagnostic Approach IEEE AccessDigital Object Identifier 10.1109/ACCESS.2024.3394541

10. S.Perumal1 and T.Velmuruga (2018) Preprocessing by Contrast Enhancement Techniques for Medical Imagesnternational Journal of Pure and Applied Mathematics Volume 118 No. 18 2018, 3681-3688ISSN: 1311-8080 (printed version); ISSN: 1314-3395 (on-line version)
11. Lesia Mochurad · Khrystyna Melnychuk· Yulianna Mochurad(2026)Optimization of brain MRI preprocessing using parallelcomputing for efficient brain tumour classification The Journal of Supercomputing (2026) 82:123 https://doi.org/10.1007/s11227-026-08282-2
12. K.Madhan. (2025). Chaotic Regime Identification in Coupled Thermo-Fluid Oscillators Under Variable Boundary Forcing. *Applied Nonlinearity in Science and Technology*, 6-12.
13. M. V. Narayana1 · J. Nageswara Rao · Sanjeev Shrivastava1 · G. S. Pradeep Ghantasala Iacovos Ioannou ·Vasos Vassiliou (2024) A framework for identification of brain tumors from MR images usingprogressive segmentation Health and Technology (2024) 14:539–556https://doi.org/10.1007/s12553-024-00844-9
14. Mojtaba Jahanian, Abbas Karimi, Nafiseh Osati Eraghi & Faraneh Zarafshan (2025) Adaptive clustering for medical image analysis using the improved separation index Scientific Reports | (2025) 15:28191 | https://doi.org/10.1038/s41598-025-13670-4
15. Felix J. Dorfner , Jay B. Patel, Jayashree Kalpathy-Cramer, Elizabeth R. erstner& Christopher P. Bridge (2025)A review of deep learning for brain tumoranalysis in MRIhttps://doi.org/10.1038/s41698-024-00789-2
16. Mojtaba Jahaniana,_, Abbas Karimia,_, Nafiseh Osati Eraghia, FaranehZarafshanb (2025) SONSC: An Adaptive Clustering Algorithm forAutomated Medical Image Analysis Using theImproved Separation Index DOI: https://doi.org/10.21203/rs.3.rs- 6667012/v1https://doi.org/10.1038/s41598-025-13670-4.